

# METRO 120ERVD-ECM

## ENERGY RECOVERY VENTILATOR



### ENGINEERING DATA

#### TOTAL RECOVERY CORE

Cross-flow energy recovery core transfers heat and water vapor between two air-streams. Easily removed for cleaning or service.

#### MOTORS AND BLOWERS

Each airstream has an independent centrifugal blower with ECM motor with multiple fan speed operations.

#### INTELLIGENT DEFROST DAMPER MOTOR

- Smart damper motor with integrated circuit board
- Energy efficient DC motor
- Power saving standby mode when not cycling
- Integrated ice breaker technology
- Temperature compensated torque for reliable operation in any application
- Auto-sensed memory storage of opened and closed positions
- Soft sealing for extended part life

#### FILTERS

Washable antimicrobial MERV 6 air filters in exhaust and supply air streams.

#### MOUNTING

Mounting brackets supplied

#### DEFROST

Recirculating damper defrost system.

#### CASE

Twenty gauge prepainted galvanized steel for superior corrosion resistance. Insulated to prevent exterior condensation.

#### ELECTRONICS

Main control can be wall mounted in a central location. 3 wire 20 gauge (min.) 100 ft. length (max.)

### OPTIONAL ACCESSORIES:

**TechGrille**  
99-EAG4  
99-EAG5  
99-EAG6  
99-EAG8



**Terminator Fitting**  
99-TM4  
99-TM5  
99-TM6



**Wireless 20/40/60 Min Timer**  
99-DET02



**Dual Hood**  
99-190  
99-194



**Weather Hoods**  
99-185  
99-186  
99-187



### LIFEBREATH CONTROL OPTIONS

FEATURES	99-DXPLO2	99-BC02	99-BC03	99-BC04
5 speed fan operation on each mode	✓			
2 speed fan operation (Low/High)		✓		✓
Continuous low speed fan operation			✓	
Humidity control through adjustable Dehumidistat	✓	✓	✓	
Large digital LCD screen	✓			
LED status indicator lights		✓	✓	✓
Continuous Ventilation	✓		✓	
Continuous Recirculation	✓		✓	
20 ON/40 OFF	✓			
10 ON/50 OFF	✓			
20 ON/40 Recirculation	✓		✓	✓
20/40/60 min. High speed override button	✓			
Compatible with 99-DET02 Wireless Timer	✓	✓	✓	✓
3 wire connection	✓	✓	✓	✓

### TIMER OPTIONS

**99-DET01 - Lifebreath 20/40/60 Minute Timer**  
Initiates high speed Ventilation for 20, 40 or 60 minutes. 3 wire connection.

**99-DET02**  
**Wireless Lifebreath 20/40/60 Minute Timer**  
Initiates high speed Ventilation for 20, 40 or 60 minutes. Wirelessly connects to main control for ease of installation. 40' approximate range. Exclusive to Lifebreath.

**99-RX02 - Wireless Lifebreath Repeater**  
Extends range of 99-DET02 Wireless Timers. Plugs into 120V power outlet. Wirelessly connects to main control and 99-DET02. Install at halfway point between timer and main wall control if timer is out of range.



99-DXPLO2



99-DET02

**LIFEBREATH**  
Indoor Air Systems

www.lifebreath.com

# METRO 120ERVD-ECM

## ENERGY RECOVERY VENTILATOR




### PERFORMANCE (HVI CERTIFIED)

IN. W.G. (PA)	0.1 (25) CFM (L/s)	0.2 (50) CFM (L/s)	0.3 (75) CFM (L/s)	0.4 (100) CFM (L/s)	0.5 (125) CFM (L/s)	0.6 (150) CFM (L/s)	0.7 (175) CFM (L/s)	0.8 (200) CFM (L/s)
Net Supply Airflow	131 (62)	124 (58)	116 (55)	108 (51)	98 (46)	87 (41)	74 (35)	58 (27)
Gross Supply Airflow	132 (63)	125 (59)	118 (56)	109 (52)	100 (47)	88 (42)	75 (35)	59 (28)
Gross Exhaust Airflow	130 (61)	122 (57)	116 (55)	110 (52)	103 (49)	93 (44)	78 (37)	57 (27)

ELECTRICAL SPECIFICATIONS	
VAC @ 60Hz	120
Watts / Low Speed	20
Watts / High Speed	78
Amp Rating	0.8

			WATTS/ CFM
Sensible Effectiveness (ASE) @ 64 CFM (30 L/s)	32°F (0°C)	81%	.410
Sensible Efficiency (SRE) @ 64 CFM (30 L/s)	32°F (0°C)	72%	.410
Sensible Efficiency (SRE) @ 49 CFM (23 L/s)	32°F (0°C)	74%	.411
Total Efficiency (TRE) @ 64 CFM (30 L/s)	95°F (35°C)	46%	.440
Sensible Efficiency (SRE) @ 57 CFM (27 L/s)	-13°F (-25°C)	57%	-




**WEIGHT:**  
57 LBS (25.8 KG)

**SHIPPING WEIGHT:**  
67 LBS (30 KG)

**NOTE:**  
Front clearance of 25 in. (635 mm) is recommended for servicing unit.



### DIMENSIONS



Date: \_\_\_\_\_  
 Tag: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Control: \_\_\_\_\_

Contractor: \_\_\_\_\_  
 Supplier: \_\_\_\_\_  
 Quote #: \_\_\_\_\_  
 Submitted By: \_\_\_\_\_  
 Timer: \_\_\_\_\_ Timer Qty: \_\_\_\_\_

### WARRANTY

Units carry a 5 year warranty on the enthalpic (ERV) core and a 5 year replacement parts warranty.

All units conform to CSA and UL standards

