

TFP 3000 HEPA

RESIDENTIAL HEPA AIR CLEANING



ENGINEERING DATA

MOTORS AND BLOWERS

High efficiency PSC Motor - 150 cfm @ .4" WC 110 watts - 120 VAC. Standard three prong plug to receptacle. The TFP is equipped with a standard power supply of 5'5" (1.6 meters) cable.

COLLECTOR AND FILTER

One replaceable TFP collector and one replaceable HEPA filter. Easy to remove for cleaning and replacement. Annual inspection recommended.

MOUNTING THE AIR CLEANER - 4 OPTIONS

1. Mount to the furnace return
2. Mount between the HRV and the furnace
3. Hang from a joist and duct to the furnace
4. Stand alone installation

OPTIONS



- 65-502R One replacement HEPA Filter
- 65-503R One replacement TFP Collector
- 99-TFP Optional Installation Kit
- Two 7 in Duct Connection Collars
- 12.5 in length of 7 in non-insulated flex duct
- Four nylon zip ties

TFP3000HEPA Particle Capture Rate

PARTICLE SIZE (MICRONS)	Percentage Caught
.3 or more	99.7%


- Model TFP3000HEPA - 99.97% efficient at .3 microns.
- A human hair is 100 microns wide.
- Spores and pollen are all larger than 8 microns.
- A micron is 1/1000 of a millimeter, or less than 1/2 of 1/10,000 of an inch.

DIMENSIONS



Note:
Minimum 16"
(406 mm) required
for service

All duct connections are 7" (178 mm)



NOTE: All specifications are subject to change without notice.

Date: _____ Contractor: _____

Tag: _____ Supplier: _____

Project: _____ Qty: _____ Quote #: _____

Engineer: _____ Submitted By: _____

Control: _____ Timer: _____ Timer Qty: _____

WARRANTY
Units carry a 5 year replacement parts warranty.
No warranty on collector/filter.

All units conform to CSA and UL standards



www.lifebreath.com